

ULV COLD FOGGER C150+

Tank Capacity	6 Liters (1.6 Gallon)
Power	220V / 110V
Motor	1170W
Flow Rate	60 LPH (16 GPH)
Droplet Size	5 - 50 microns
Net Weight	4.7 kg (10.4 lb)
Dimensions (cm)	62 x 31 x 17
Dimensions (inch)	24.4 x 12.2 x 6.7



VectorFog’s flagship ULV cold fogger, the C150+, is ideal for indoor as well as outdoor applications. With its large 6 liters (1.59 Gal.) tank, this fogger can cover a large area without the need of refilling. Thanks to its fully adjustable droplet size between 5 - 50 microns, this fogger can be used to apply disinfectants, biocides and insecticides in a multitude of locations. With its powerful 1170 Watt motor, this fogger provides years of durability and performance. More technical information is available on page 6.

TRUCK MOUNTED ULV FOGGER TU100N

Tank Capacity	130 Liters (34.3 Gallon)
Engine	Keyang G710L
Fuel	Gasoline
Fuel Tank	5 Liters (1.32 Gallon)
Spray Distance	8 meters (26.2 ft.)
Net Weight	90 kg (198.4 lb)
Dimensions (cm)	111 x 72 x 76
Dimensions (inch)	43.7 x 28.3 x 29.9



The Vectorfog™ truck mounted ULV fogger TU100N is ideal for large scale applications including vector control and agricultural fumigation. Features include a 7.0 Hp Keyang engine, a 130 liters (34.3 Gal.) tank, a head with 3 nozzles and a remote control. With a horizontal spray distance of 8 meters (26.2 ft.), this fogger sprays a large area in a minimal amount of time.